

Safety Brief: Aerial/Scissor Lifts Work

Rules and Requirements

- All operators must be certified
- All operators must receive site specific orientation (Can be supplied by GC)
 - Hazards
- All lifts must be inspected prior to first use of the day
 - Inspections must be documented
 - Inspections must be submitted to GC daily
- **Operation**
 - **All Lifts**
 - Always keep gate or chain closed
 - Never stand above actual work platform
 - No ladders, buckets, etc. to get taller
 - Exception: User is tied off properly to structure above
 - No modifications without mfg. approval
 - Never tie cords, hoses, etc. to lift
 - If lift is being used for access, worker must be tied off to the basket or the structure before exiting the basket.
 - When using lift for access, worker must be able to walk onto the working surface. (No climbing out of basket).
 - Never use it as a crane
 - Material may be lifted on the lift if it doesn't exceed the rating and is not tied to the lift
 - Set up on firm level ground
 - Remove keys at end of shift
 - Always review manual upon first use
 - Manual must be on board
 - Other than airing tires, all maintenance by vendor
 - **Aerial Lifts**
 - Harness and 3' lanyard or diablo yoyo must be worn at all times
 - No maintenance while in operation
 - While moving the lift, raise the basket to a height where you can see 360 degrees

Safety Brief: Aerial/Scissor Lifts Work
